## PLUMETT SUPERJET

The SuperJet<sup>™</sup> is designed for blowing or floating telecommunication cables (optical fibre, coax or multipair) or micro-ducts in preinstalled ducts.

## STANDARD EQUIPMENT

1 box for the SuperJet

1 box for tools, inserts, wear parts and consumables (seals, lubricant, etc.)

1 set of tools

1 speed and distance indicator

1 air hose  $1\frac{1}{2}$ " (10 m) and stop valve to connect to compressor

2 bottles of lubricant Jetting Lube

1 operation and maintenance manual



## **VISION & PERFORMANCE**

Standard Version	SuperJet with hydraulic drive	SuperJet with pneumatic drive
Туре	HO1	PO1
Cable dia. [mm]	9-32	9-22
Duct OD [mm]	20-63	20-63
Drive unit	Hydraulic	Pneumatic
Max air consumption of motor [m3/min]	-	1 (at 4 bar)
Pushing force [N]	0-700	0-600
Linear pressure on cable [N/cm]	0-94	0-94
Max speed [m]	60	60
Hydraulic power pack type of engine	Honda Gasoline GX200	-
Hydraulic power pack engine max power [kw]	4.1	-
Hydraulic power pack engine max speed rpm [min-1]	3600	-
Hydraulic power pack pump delivery rating [l/m]	17	-
Hydraulic power pack pump hydraulic pressure [bar]	70	-
Max air pressure [bar]	12	12
Max water pressure [bar]	25	25
Dimension of apparatus I x w x h [mm]	915 x 260 x 410	900 x 345 x 350
Dimension of apparatus with case I x w x h [mm]	970 x 380 x 440	960 x 370 x 435
Dimension of tools and accessories case I x w x h [mm]	585 x 385 x 250	550 x 350 x 250
Weight of machine [kg]	37	35
Total weight [kg]	152	67

Specifications are subject to change without notice



## MAIN ACCESSORIES



**Hydrocab-080**, accessory for cable installation with water (floating), 80 l/min



**Air after-cooler**, to increase Jetting performances when ambient temperature is over 20°C



**Jetting Lube**, lubricant improving Jetting performance



**Lubricator L18**, for the continuous lubrication of cables for a better Jetting performance



**Figaro**, intermediate cable storage system, avoiding figure of 8



**Y-connector**, for the installation of cable into an occupied duct



**Sonic head**, for the installation of cables with low stiffness



**Multi-duct accessories**, for the installation of microduct bundles



